

| | MATERIAL SAFETY DATA | SHEET | |
|-------------------------------|---|---|--|
| Product Name: | Pure50+ Epoxy Adhesive | | |
| Description: | Epoxy adhesive for anchoring in co | oncrete and rebar dowelling | |
| Supplier: | Powers Fasteners, Inc. 2 Powers | - | |
| Customer Service: | 800-524-3244 | | |
| Emergency Phone: | (CHEMTREC) Within USA: (800) 424-9300; Outside USA: 01 (703) 527-3887 | | |
| | INGREDIENTS | | |
| Part A: (White Component) | | CAS Number | |
| Epoxy Resin Blend | | TS | |
| | -2-hydroxymethyl- polymer | 30499-70-8 | |
| Quartz Sand | , | 14808-60-7 | |
| | | | |
| Part B: (Dark Gray Component) | | | |
| Proprietary blend of am | ne curing agents | TS | |
| m-Xylylenediamine | - | 1477-55-0 | |
| Phenol | | 108-95-2 | |
| Quartz Sand | | 14808-60-7 | |
| Abbreviations: NE= Not | established TS= 1 | Frade Secret of Supplier | |
| | SAFE USAGE RECOMMEND | | |
| Ventilation: | Use with adequate ventilation, eith | er natural or mechanical. | |
| Eye Protection: | Avoid eye contact. Wear safety glasses with side shields. | | |
| Skin Protection: | Avoid skin contact. Wear neoprene or rubber gloves. | | |
| Respiratory Protection: | None usually required. To protect t | from dust and odors, or where | |
| | ventillation is inadequate, wear a d | | |
| | resipitator with organic vapor cartri | | |
| | resipitator with organic vapor cartin | | |
| Notice: | For professional use. Keep away | from children. | |
| | EMERGENCY AND FIRST AID PR | ROCEDURES | |
| Eyes: | Immediately flush eyes with plenty of | water for at least 15 minutes and | |
| | cont a physician. | | |
| Skin: | Wash with soap and water. Launder clothing before reuse. | | |
| | Seek medical attention if any sympton | ns develop. | |
| Inhalation: | If uncomfortable, move to fresh air. Contact a physician if symptoms persist. | | |
| Ingestion: | Contact a physician immediately, and | rinse mouth with water. Then drink | |
| | | omiting unless directed by a physician. | |
| Other: | Contact a physician if there is any que | | |
| | exposure. | | |
| | HEALTH HAZARD INFORM | | |
| Potential Hazards: | Part A: Can be irritating to the eye | | |
| r vieniliai Mazai US. | • • | - | |
| | and swelling can occur with some | individuals. | |

Part B: Can be irritating to eyes and skin. Vapors can be irritatiing.

| 6 | | PHYSICAL CHARACTERISTICS | | |
|---------|--|--|--------|--|
| 0 | | | | |
| | Appearance and Odor: | Part A: White paste | | |
| | | Part B: Dark Gray Paste | | |
| | Boiling Point: | Greater than 212° F. | | |
| | (Air=1) Vapor Density: | >1 | | |
| | (Water=1) Evaporation Rate: | <1 | | |
| | Specific Gravity: | 1.5 (Mixed) | | |
| | VOC Content: | 0.0 g/l | | |
| | Odor: | Sweet, amine-like | | |
| | Solubility in Water: | Insoluble | | |
| | pH: | NE | | |
| 7 | | FIRE, HAZARD AND REACTIVITY DATA | | |
| | Flammability: | Non-flammable. Flash Point: | >250°F | |
| | - | Boiling Point: | >212°F | |
| | Stability: | Stable. Hazardous polymerization will not occur. | | |
| | Incompatibility: | Strong acids and oxidizers. | | |
| | Unusual fire or | | | |
| | Explosion Hazards: | None Known. | | |
| | Extinguishing Media: | CO ₂ , Dry Chemical, Foam, Water spray. | | |
| | Fire Fighting: | | | |
| | Thermal Decomposition | Self-contained breathing equipment recommended. | | |
| | Products: | May occur, including COx, NOx | | |
| 8 | | SPORTATION AND REGULATORY INFORMATION | | |
| 0 | Hazard Communication: This MSDS has been prepared in accordance with the federal | | | |
| | | OSHA Hazard Communication Standard 29 CFR 1910. 1200. | | |
| | HMIS Codes: | Health: 2; Flammability: 0; Physical Hazard: 1 PPE: B | | |
| | | | | |
| | US DOT Proper Shipping Name: | roper Shipping Name: Consumer commodity. ORM-D | | |
| | | AMINES, solid, corrosive, n.o.s. (m-Xylylenediamine) | | |
| | | UN 3259 Class: 8 PG: III | | |
| | IATA/ICAO Proper Shipping Name: | AMINES, solid, corrosive, n.o.s. (m-Xylylenediamine) | | |
| | 1 11 0 | UN 3259 Class: 8 PG: III | | |
| | Packing Instructions: | Limited Quantity: Y 845 | | |
| | Ũ | Passenger Aircraft: 860 | | |
| | | Cargo Aircraft Only: 864 | | |
| | IMO/IMDG Proper Shipping Name: | AMINES, solid, corrosive, n.o.s. m-Xylylenediamine)) | | |
| | UN 3259 Class: 8 PG: III EmS: F-A, S-B | | | |
| | TSCA Inventory Status: Chemical components listed on TSCA inventory. | | | |
| | SARA Title III, Section 313: | | | |
| | | reporting under Section 313 of SARA Title III (40 CFR Part 372). | | |
| | EPA Waste Code(s): | Phenol is considered a hazardous waste. | | |
| 9 | | STORAGE, CLEAN-UP, AND DISPOSAL | | |
| | Storage: | Store in a cool, dry place. Keep from freezing and extreme heat, which may | | |
| | | shorten shelf life. | | |
| Spills: | | Collect spilled contents with absorbent material and place in a sealable | | |
| - | | container for proper disposal. | | |
| | | | | |
| | Waste Disposal: | Dispose of in accordance with federal, state and local regulations. | | |

The information and recommendations provided herin are based on information available to us at the time of preparation. We make no other warranty, expressed or implied, as to its correctness, completeness, or as to the results and reliance of the information.

