SAFETY DATA SHEET

MS-SW

Section 1. Identification Product name : Mineral Spirits : MS-SW **Product code** : Not available. Other means of identification **Product type** : Liquid. Relevant identified uses of the substance or mixture and uses advised against Not applicable. Manufacturer : THE SHERWIN-WILLIAMS COMPANY 101 W. Prospect Avenue Cleveland, OH 44115 **Emergency telephone** : (216) 566-2917 number of the company **Product Information** : Not available. **Telephone Number Regulatory Information** : (216) 566-2902 **Telephone Number Transportation Emergency** : (800) 424-9300 **Telephone Number**

Section 2. Hazards identification

OSHA/HCS status	 This material is considered hazardous by the OSHA Hazard Communication Standard (29 CFR 1910.1200).
Classification of the substance or mixture	 FLAMMABLE LIQUIDS - Category 3 SPECIFIC TARGET ORGAN TOXICITY (SINGLE EXPOSURE) (Respiratory tract irritation) - Category 3 SPECIFIC TARGET ORGAN TOXICITY (SINGLE EXPOSURE) (Narcotic effects) - Category 3 SPECIFIC TARGET ORGAN TOXICITY (REPEATED EXPOSURE) - Category 2 ASPIRATION HAZARD - Category 1
GHS label elements	
Hazard pictograms	
Signal word	: Danger
Hazard statements	: Flammable liquid and vapor.

 Flammable liquid and vapor.
May be fatal if swallowed and enters airways.
May cause respiratory irritation.
May cause drowsiness or dizziness.
May cause damage to organs through prolonged or repeated exposure.

Precautionary statements

Section 2. Hazards identification

Prevention	: Wear protective gloves. Wear eye or face protection. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Use explosion-proof electrical, ventilating, lighting and all material-handling equipment. Use only non-sparking tools. Take precautionary measures against static discharge. Keep container tightly closed. Use only outdoors or in a well-ventilated area. Do not breathe vapor.
Response	: Get medical attention if you feel unwell. IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER or physician if you feel unwell. IF SWALLOWED: Immediately call a POISON CENTER or physician. Do NOT induce vomiting. IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water or shower.
Storage	: Store locked up. Store in a well-ventilated place. Keep cool.
Disposal	 Dispose of contents and container in accordance with all local, regional, national and international regulations.
Supplemental label elements	DELAYED EFFECTS FROM LONG TERM OVEREXPOSURE. Contains solvents which can cause permanent brain and nervous system damage. Intentional misuse by deliberately concentrating and inhaling the contents can be harmful or fatal. FOR INDUSTRIAL USE ONLY.
	Please refer to the SDS for additional information. Keep out of reach of children. Do not transfer contents to other containers for storage.
Hazards not otherwise classified	: None known.

Section 3. Composition/information on ingredients

Substance/mixture	: Substance
Other means of	: Not available.
identification	

CAS number/other identifiers

Ingredient name	% by weight	CAS number
Med. Aliphatic Hydrocarbon Solvent	100	64742-88-7

Any concentration shown as a range is to protect confidentiality or is due to batch variation.

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health and hence require reporting in this section.

Occupational exposure limits, if available, are listed in Section 8.

Section 4. First aid measures

Description of necessary first aid measures

Eye contact	 Immediately flush eyes with plenty of water, occasionally lifting the upper and lower eyelids. Check for and remove any contact lenses. Continue to rinse for at least 10 minutes. Get medical attention following exposure or if feeling unwell.
Inhalation	: Remove victim to fresh air and keep at rest in a position comfortable for breathing. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Get medical attention. If necessary, call a poison center or physician. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.
Skin contact	: Flush contaminated skin with plenty of water. Remove contaminated clothing and shoes. Continue to rinse for at least 10 minutes. Get medical attention following exposure or if feeling unwell. Wash clothing before reuse. Clean shoes thoroughly before reuse.

Date of issue/Date of revision : 6/20/2016	Date of previous issue	:6/4/2016	Version : 2.01	2/11
--	------------------------	-----------	----------------	------

Section 4. First aid measures

Ingestion	: Get medical attention immediately. Call a poison center or physician. Wash out mouth with water. Remove dentures if any. Remove victim to fresh air and keep at rest in a position comfortable for breathing. If material has been swallowed and the exposed person is conscious, give small quantities of water to drink. Stop if the exposed person feels sick as vomiting may be dangerous. Aspiration hazard if swallowed. Can enter lungs and cause damage. Do not induce vomiting. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Never give anything by mouth to an unconscious person. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.	
Most important symptoms/	effects, acute and delayed	
Potential acute health effe		
Eye contact	: No known significant effects or critical hazards.	
Inhalation	 Can cause central nervous system (CNS) depression. May cause drowsiness or dizziness. May cause respiratory irritation. 	
Skin contact	: No known significant effects or critical hazards.	
Ingestion	 Can cause central nervous system (CNS) depression. May be fatal if swallowed and enters airways. 	
Over-exposure signs/sym	<u>ptoms</u>	
Eye contact	: No specific data.	
Inhalation	: Adverse symptoms may include the following: respiratory tract irritation coughing nausea or vomiting headache drowsiness/fatigue dizziness/vertigo unconsciousness	
Skin contact	: No specific data.	
Ingestion	: Adverse symptoms may include the following: nausea or vomiting	
Indication of immediate me	dical attention and special treatment needed, if necessary	
Notes to physician	 Treat symptomatically. Contact poison treatment specialist immediately if large quantities have been ingested or inhaled. 	
Specific treatments	: No specific treatment.	
Protection of first-aiders	: No action shall be taken involving any personal risk or without suitable training. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation.	

See toxicological information (Section 11)

Section 5. Fire-fighting measures

Extinguishing media	
Suitable extinguishing media	: Use dry chemical, CO ₂ , water spray (fog) or foam.
Unsuitable extinguishing media	: Do not use water jet.

: 6/20/2016 Date of previous issue

Section 5. Fire-fighting measures

	carbon monoxide
Special protective actions for fire-fighters	: Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training. Move containers from fire area if this can be done without risk. Use water spray to keep fire-exposed containers cool.
Special protective equipment for fire-fighters	: Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.

Section 6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

For non-emergency personnel	: No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilled material. Shut off all ignition sources. No flares, smoking or flames in hazard area. Avoid breathing vapor or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment.
For emergency responders	: If specialized clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".
Environmental precautions	: Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air).
Methods and materials for co	ntainment and cleaning up
Small spill	: Stop leak if without risk. Move containers from spill area. Use spark-proof tools and explosion-proof equipment. Dilute with water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.
Large spill	: Stop leak if without risk. Move containers from spill area. Use spark-proof tools and explosion-proof equipment. Approach release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations (see Section 13). Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilled product. Note: see Section 1 for emergency contact information and Section 13 for waste disposal.

Section 7. Handling and storage

Precautions for safe handling

Section 7. Handling and storage

	-
Protective measures	Put on appropriate personal protective equipment (see Section 8). Do not breathe vapor or mist. Do not swallow. Avoid contact with eyes, skin and clothing. Use only with adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Do not enter storage areas and confined spaces unless adequately ventilated. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Store and use away from heat, sparks, open flame or any other ignition source. Use explosion-proof electrical (ventilating, lighting and material handling) equipment. Use only non-sparking tools. Take precautionary measures against electrostatic discharges. Empty containers retain product residue and can be hazardous. Do not reuse container.
Advice on general occupational hygiene	Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.
Conditions for safe storage, including any incompatibilities	Store in accordance with local regulations. Store in a segregated and approved area. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Store locked up. Eliminate all ignition sources. Separate from oxidizing materials. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabeled containers. Use appropriate containment to avoid environmental contamination.

Section 8. Exposure controls/personal protection

Control parameters

Occupational exposure limits (OSHA United States)

Ingredient name	Exposure limits
Med. Aliphatic Hydrocarbon Solvent	OSHA PEL (United States, 2/2013). TWA: 100 ppm 8 hours. TWA: 400 mg/m ³ 8 hours.

Occupational exposure limits (Canada)

Ingredient name	Exposure limits
Med. Aliphatic Hydrocarbon Solvent	CA Quebec Provincial (Canada, 1/2014). TWAEV: 400 ppm 8 hours. TWAEV: 1590 mg/m ³ 8 hours.

Appropriate engineering controls Environmental exposure	other engineer recomment vapor or o ventilation	vith adequate ventilation. neering controls to keep nded or statutory limits. ust concentrations below equipment.	worker exposure to a The engineering con any lower explosive	airborne contam trols also need to e limits. Use exp	inants belo o keep gas losion-proc	w any , of
controls	they comp cases, fur will be neo	from ventilation or work by with the requirements ne scrubbers, filters or en cessary to reduce emission	of environmental prongineering modificati	otection legislation ons to the proce	on. In some	e
Hygiene measures	eating, sm Appropria Wash cor	ds, forearms and face th oking and using the lava te techniques should be taminated clothing befor re close to the workstation	itory and at the end o used to remove pote e reusing. Ensure th	of the working pentially contamination	eriod. ated clothin	g.
Date of issue/Date of revision	: 6/20/2016	Date of previous issue	: 6/4/2016	Version	: 2.01	5/11

Section 8. Exposure controls/personal protection

	• •			
Eye/face protection	Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gases or dusts. If contact is possible, the following protection should be worn, unless he assessment indicates a higher degree of protection: safety glasses with side-shields.			
Skin protection				
Hand protection	: Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves cannot be accurately estimated.			
Body protection	: Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product. When there is a risk of ignition from static electricity, wear anti-static protective clothing. For the greatest protection from static discharges, clothing should include anti-static overalls, boots and gloves.			
Other skin protection	: Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.			
Respiratory protection	: Based on the hazard and potential for exposure, select a respirator that meets the appropriate standard or certification. Respirators must be used according to a respiratory protection program to ensure proper fitting, training, and other important aspects of use.			

Section 9. Physical and chemical properties

Appearance

Appearance		
Physical state	:	Liquid.
Color	1	Not available.
Odor	1	Not available.
Odor threshold	1	Not available.
рН	:	Not available.
Melting point	:	Not available.
Boiling point	1	148°C (298.4°F)
Flash point	1	Closed cup: 38°C (100.4°F) [Pensky-Martens Closed Cup]
Evaporation rate	1	0.13 (butyl acetate = 1)
Flammability (solid, gas)	1	Not available.
Lower and upper explosive (flammable) limits	1	Lower: 1% Upper: 6%
Vapor pressure	1	0.023 kPa (0.169 mm Hg) [at 20°C]
Vapor density	4	5 [Air = 1]
Relative density	4	0.77
Solubility	1	Not available.
Partition coefficient: n- octanol/water	1	Not available.
Auto-ignition temperature	1	Not available.
Decomposition temperature	1	Not available.
Viscosity	1	Kinematic (room temperature): <0.205 cm²/s (<20.5 cSt) Kinematic (40°C (104°F)): <0.205 cm²/s (<20.5 cSt)
Molecular weight	1	Not applicable.
Aerosol product		
Date of issue/Date of revision		: 6/20/2016 Date of previous issue : 6/4/2016 Version : 2.01 6/11

Section 9. Physical and chemical properties

Heat of combustion : 41.2 kJ/g

Section 10. Stability and reactivity

Reactivity	: No specific test data related to reactivity available for this product or its ingredients.
Chemical stability	: The product is stable.
Possibility of hazardous reactions	: Under normal conditions of storage and use, hazardous reactions will not occur.
Conditions to avoid	: Avoid all possible sources of ignition (spark or flame). Do not pressurize, cut, weld, braze, solder, drill, grind or expose containers to heat or sources of ignition. Do not allow vapor to accumulate in low or confined areas.
Incompatible materials	: Reactive or incompatible with the following materials: oxidizing materials
Hazardous decomposition products	: Under normal conditions of storage and use, hazardous decomposition products should not be produced.

Section 11. Toxicological information

Information on toxicological effects

Acute toxicity

Not available.

Irritation/Corrosion

Not available.

Sensitization

Not available.

Mutagenicity

Not available.

Carcinogenicity

Not available.

Reproductive toxicity

Not available.

Teratogenicity

Not available.

Specific target organ toxicity (single exposure)

Name		Route of exposure	Target organs
Med. Aliphatic Hydrocarbon Solvent	Category 3		Respiratory tract irritation and Narcotic effects

Specific target organ toxicity (repeated exposure)

Name			Catego		Route of exposure	Tar	get organs	
Med. Aliphatic Hydrocarbon	Solvent		Catego	ry 2	Not determined	Not	determined	
Date of issue/Date of revision	: 6/20/2016	Date of previous	issue	: 6/4/2016	ş 1	/ersion	: 2.01	7/11

Section 11. Toxicological information

Aspiration hazard

Name	Result
Med. Aliphatic Hydrocarbon Solvent	ASPIRATION HAZARD - Category 1

Information on the likely routes of exposure	: Not available.					
Potential acute health effe	<u>cts</u>					
Eye contact	: No known significant effects or critical hazards.					
Inhalation	Can cause central nervous system (CNS) depression. May cause drowsiness or dizziness. May cause respiratory irritation.					
Skin contact	: No known significant effects or critical hazards.					
Ingestion	: Can cause central nervous system (CNS) depression. May be fatal if swallowed and enters airways.					
Symptoms related to the p	hysical, chemical and toxicological characteristics					
Eye contact	: No specific data.					
Inhalation	: Adverse symptoms may include the following: respiratory tract irritation coughing nausea or vomiting headache drowsiness/fatigue dizziness/vertigo unconsciousness					
Skin contact	: No specific data.					
Ingestion	: Adverse symptoms may include the following: nausea or vomiting					
Delayed and immediate eff	fects and also chronic effects from short and long term exposure					
Short term exposure						
Potential immediate effects	: Not available.					
Potential delayed effects	: Not available.					
Long term exposure						
Potential immediate effects	: Not available.					
Potential delayed effects	: Not available.					
Potential chronic health ef	ffects					
Not available.						
General	: May cause damage to organs through prolonged or repeated exposure.					
Carcinogenicity	: No known significant effects or critical hazards.					
Mutagenicity	: No known significant effects or critical hazards.					
Teratogenicity	: No known significant effects or critical hazards.					
Developmental effects	: No known significant effects or critical hazards.					
Fertility effects	: No known significant effects or critical hazards.					
	. No known significant creets of childa hazards.					
Numerical measures of top						

Acute toxicity estimates

Date	of	issue/	Date	of	revi	ision

: 6/20/2016

Section 12. Ecological information

Toxicity

Not available.

Persistence and degradability

Not available.

Bioaccumulative potential

Not available.

Mobility in soil

Soil/water partition	: Not available.
coefficient (Koc)	

Other adverse effects : No known significant effects or critical hazards.

Section 13. Disposal considerations

Disposal methods

The generation of waste should be avoided or minimized wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible. This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Vapor from product residues may create a highly flammable or explosive atmosphere inside the container. Do not cut, weld or grind used containers unless they have been cleaned thoroughly internally. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

Section 14. Transport information

	DOT Classification	TDG Classification	Mexico Classification	ΙΑΤΑ	IMDG
UN number	UN1263	UN1263	UN1263	UN1263	UN1263
UN proper shipping name	PAINT RELATED MATERIAL				
Transport hazard class(es)	3	3	3	3	3
Packing group	III	Ш	ш	ш	ш
Environmental hazards	No.	No.	No.	No.	No.
I I I I I Date of issue/Date of revision : 6/20/2016 Date of previous issue : 6/4/2016 Version : 2.01 9/1					

Additional	This product may	Product classified	-	-	Emergency
"C Li tra Ve N pa th	be re-classified as	as per the			schedules (EmS
	"Combustible	following sections of the Transportation of Dangerous Goods Regulations: 2. 18-2.19 (Class 3).			F-E, S-E
	Liquid," unless transported by				
	vessel or aircraft.				
	Non-bulk				
	packages (less				
	than or equal to 119 gal) of				
	combustible				
	liquids are not				
	regulated as hazardous				
	materials.				
	ERG No.	ERG No.	ERG No.		
	128	128	128		
Special precaution	consic mode suitab	modal shipping descr der container sizes. T of transport (sea, air ly for that mode of tra	he presence of a sh , etc.), does not indic	ipping description fo cate that the product g must be reviewed	r a particular t is packaged l for suitability
	respo unload	o shipment, and com nsibility of the person ding dangerous good ances and on all actio	s must be trained or	for transport. Peop all of the risks deriv	le loading and
o Annex II of MA	according : Not ava	nsibility of the person ding dangerous good ances and on all actio	offering the product s must be trained or	for transport. Peop all of the risks deriv	le loading and
o Annex II of MA	according : Not ava	nsibility of the person ding dangerous good ances and on all actio	offering the product s must be trained or	for transport. Peop all of the risks deriv	le loading and
Transport in bulk to Annex II of MA the IBC Code	according : Not ava	nsibility of the person ding dangerous good ances and on all actio ailable. Shipping name	offering the product is must be trained or ons in case of emerg	for transport. Peop all of the risks deriv	le loading and

Section 15. Regulatory information

SARA 313


SARA 313 (40 CFR 372.45) supplier notification can be found on the Environmental Data Sheet.

California Prop. 65

Not applicable.

Section 16. Other information

Hazardous Material Information System (U.S.A.)



The customer is responsible for determining the PPE code for this material.

Caution: HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks Although HMIS® ratings are not required on SDSs under 29 CFR 1910. 1200, the preparer may choose to provide them. HMIS® ratings are to be used with a fully implemented HMIS® program. HMIS® is a registered mark of the National Paint & Coatings Association (NPCA). HMIS® materials may be purchased exclusively from J. J. Keller (800) 327-6868.

Procedure used to derive the classification

Date of issue/Date of revision	: 6/20/2016	Date of previous issue	: 6/4/2016	Version : 2.01	10/11
--------------------------------	-------------	------------------------	------------	----------------	-------

Section 16. Other information

Classification

FLAMMABLE LIQUIDS - Category 3 SPECIFIC TARGET ORGAN TOXICITY (SINGLE EXPOSURE) (Respiratory tract irritation) - Category 3 SPECIFIC TARGET ORGAN TOXICITY (SINGLE EXPOSURE) (Narcotic effects) - Category 3 SPECIFIC TARGET ORGAN TOXICITY (REPEATED EXPOSURE) - Category 2 ASPIRATION HAZARD - Category 1

Justification

On basis of test data Calculation method

Calculation method

Calculation method

Calculation method

<u>History</u>	
Date of printing	: 6/20/2016
Date of issue/Date of revision	: 6/20/2016
Date of previous issue	: 6/4/2016
Version	: 2.01
Key to abbreviations	: ATE = Acute Toxicity Estimate BCF = Bioconcentration Factor GHS = Globally Harmonized System of Classification and Labelling of Chemicals IATA = International Air Transport Association IBC = Internediate Bulk Container IMDG = International Maritime Dangerous Goods LogPow = logarithm of the octanol/water partition coefficient MARPOL = International Convention for the Prevention of Pollution From Ships, 1973 as modified by the Protocol of 1978. ("Marpol" = marine pollution) UN = United Nations

Notice to reader

It is recommended that each customer or recipient of this Safety Data Sheet (SDS) study it carefully and consult resources, as necessary or appropriate, to become aware of and understand the data contained in this SDS and any hazards associated with the product. This information is provided in good faith and believed to be accurate as of the effective date herein. However, no warranty, express or implied, is given. The information presented here applies only to the product as shipped. The addition of any material can change the composition, hazards and risks of the product. Products shall not be repackaged, modified, or tinted except as specifically instructed by Sherwin-Williams, including but not limited to the incorporation of non Sherwin-Williams products or the use or addition of products in proportions not specified by Sherwin-Williams. Regulatory requirements are subject to change and may differ between various locations and jurisdictions. The customer/buyer/user is responsible to ensure that his activities comply with all country, federal, state, provincial or local laws. The conditions for use of the product are not under the control of the manufacturer; the customer/buyer/user is responsible to determine the conditions necessary for the safe use of this product. The customer/buyer/user should not use the product for any purpose other than the purpose shown in the applicable section of this SDS without first referring to the supplier and obtaining written handling instructions. Due to the proliferation of sources for information such as manufacturer-specific SDS, the manufacturer cannot be responsible for SDSs obtained from any other source.

: 6/4/2016